





STONEDEKS SYSTEM
14600 COMMERCE ST. N.E.
ALLIANCE, OH 44601
PHONE: (330) 821-4299
www.silcasystem.com




SILCA GRATE SUPPORT LEDGER ATTACHMENT FOR RETRO-FIT APPLICATION.
TABLE LISTS SCREW SPACING IN INCHES TO ATTACH 2X4 LEDGER TO EACH FACE OF EXISTING JOISTS.

	NATURAL STONE OR MANUFACTURED CONCRETE PAVER THICKNESS				
	3/4"	1 1/4"	2"	2 1/2"	3"
SCREW SPACING	18"	16"	14"	13"	12"

NOTES:

1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
2. DO NOT SCALE DRAWING.
3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY. THIS DRAWING MAY NOT BE USED FOR CONSTRUCTION.
4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 4390-003A.



APPLICATION DETAILS

RESURFACE SECTION VIEWS